

	Seat Height	Arm Height	W	D	H	Fabric	Leather	Weight	Cubes/Qty
<b>i.a.m.</b>	17¼-21½"	-	21¼"	24"	33½-37¾"	1.75 yds.	24.0'	50 lbs.	28.98'/1
	438-546mm	-	540 mm	610 mm	851-959 mm	1.6 m	2.2 sqm	22.7 kg	.82 cu.



COM	COL	1	2	3	4	5	6	7	8	9	10	11
1040	1075	1184	1200	1214	1221	1231	1243	1254	1272	1301	1328	1412

- 586 Armless - Polished Aluminum Base**
- 587 Armless - Matte Black Powdercoat Base**

Fully upholstered swivel chair. Gas pneumatic lift. Adjustable height. Seat: Width 20¼" 514mm at center, Depth 17½" 445mm.

Seat: Soft urethane foam molded over rigid urethane and steel.

Backs: Outback standard with saddle stitch detail around the perimeter for fabric upholstered shells. Leather and leather alternative upholstered shells have saddle stitching accentuating the "V" detail on outback. \*All **COM/COL** fabrics must be preapproved by Bernhardt Design prior to application.

Base: Polished aluminum or matte black powdercoat. Swivel/tilt mechanism and gas pneumatic lift with 4¼" 108mm stroke mounted on 26¾" 680mm 5-star cast aluminum base with polished or black finish. Black dual wheel casters with caps coordinating with base finish. Approved for GSA. Contract GS-27F-010GA. GREENGUARD Certified.

	Seat Height	Arm Height	W	D	H	Fabric	Leather	Weight	Cubes/Qty
<b>i.a.m.</b>	17¼-21½"	24-28¼"	23"	24"	33½-37¾"	1.75 yds.	24.0'	50 lbs.	28.98'/1
	438-546mm	610-718 mm	584 mm	610 mm	851-959 mm	1.6 m	2.2 sqm	22.7 kg	.82 cu.



COM	COL	1	2	3	4	5	6	7	8	9	10	11
1144	1179	1288	1304	1318	1325	1335	1347	1358	1376	1405	1432	1516

- 588 Arm and Base - Polished Aluminum**
- 589 Arm and Base - Matte Black Powdercoat**

Fully upholstered swivel chair. Gas pneumatic lift. Adjustable height. Seat: Width 20¼" 514mm at center, Depth 17½" 445mm.

Seat: Soft urethane foam molded over rigid urethane and steel.

Backs: Outback standard with saddle stitch detail around the perimeter for fabric upholstered shells. Leather and leather alternative upholstered shells have saddle stitching accentuating the "V" detail on outback. \*All **COM/COL** fabrics must be preapproved by Bernhardt Design prior to application.

Arm and Base: Polished aluminum or matte black powdercoat. Swivel/tilt mechanism and gas pneumatic lift with 4¼" 108mm stroke mounted on 26¾" 680mm 5-star cast aluminum base with polished or black finish. Black dual wheel casters with caps coordinating with base finish. Approved for GSA. Contract GS-27F-010GA. GREENGUARD Certified.