

Seat Height	Arm Height	W	D	H	Fabric	Leather	Weight	Cubes/Qty
17¼-21½"	-	21¼"	24"	33½-37¾"	1.75 yds.	24.0'	50 lbs.	28.98'/1
438-546mm	-	540 mm	610 mm	851-959 mm	1.6 m	2.2 sqm	22.7 kg	.82 cu.

I.a.m.



GREENGUARD Certified

COM	COL	1	2	3	4	5	6	7	8	9	10	11
1000	1035	1144	1160	1174	1181	1191	1203	1214	1232	1261	1288	1372

586 Armless - Polished Aluminum Base

587 Armless - Matte Black Powdercoat Base

Fully upholstered swivel chair. Gas pneumatic lift. Adjustable height. Seat: Width 20¼" 514mm at center, Depth 17½" 445mm.

Seat: Soft urethane foam molded over rigid urethane and steel.

Backs: Outback standard with saddle stitch detail around the perimeter for fabric upholstered shells. Leather and leather alternative upholstered shells have saddle stitching accentuating the "V" detail on outback. *All **COM/COL** fabrics must be preapproved by Bernhardt Design prior to application.

Base: Polished aluminum or matte black powdercoat. Swivel/tilt mechanism and gas pneumatic lift with 4¼" 108mm stroke mounted on 26¾" 680mm 5-star cast aluminum base with polished or black finish. Black dual wheel casters with caps coordinating with base finish.

I.a.m.



GREENGUARD Certified

Seat Height	Arm Height	W	D	H	Fabric	Leather	Weight	Cubes/Qty
17¼-21½"	24-28¼"	23"	24"	33½-37¾"	1.75 yds.	24.0'	50 lbs.	28.98'/1
438-546mm	610-718 mm	584 mm	610 mm	851-959 mm	1.6 m	2.2 sqm	22.7 kg	.82 cu.

COM	COL	1	2	3	4	5	6	7	8	9	10	11
1100	1135	1244	1260	1274	1281	1291	1303	1314	1332	1361	1388	1472

588 Arm and Base - Polished Aluminum

589 Arm and Base - Matte Black Powdercoat

Fully upholstered swivel chair. Gas pneumatic lift. Adjustable height. Seat: Width 20¼" 514mm at center, Depth 17½" 445mm.

Seat: Soft urethane foam molded over rigid urethane and steel.

Backs: Outback standard with saddle stitch detail around the perimeter for fabric upholstered shells. Leather and leather alternative upholstered shells have saddle stitching accentuating the "V" detail on outback. *All **COM/COL** fabrics must be preapproved by Bernhardt Design prior to application.

Arm and Base: Polished aluminum or matte black powdercoat. Swivel/tilt mechanism and gas pneumatic lift with 4¼" 108mm stroke mounted on 26¾" 680mm 5-star cast aluminum base with polished or black finish. Black dual wheel casters with caps coordinating with base finish.