

I.a.m.



Seat Height	Arm Height	W	D	H	Fabric	Leather	Weight	Cubes/Qty
17¼-21½"	-	21¼"	24"	33½-37¾"	1.75 yds.	24.0'	50 lbs.	28.98' / 1
438-546 mm	-	540 mm	610 mm	851-959 mm	1.6 m	2.2 sqm	22.7 kg	.82 cu.

COM	COL	1	2	3	4	5	6	7	8	9	10	11
1137	1172	1262	1281	1305	1318	1332	1340	1351	1369	1398	1425	1509

586 Armless. Polished Aluminum Base

587 Armless. Matte Black Powdercoat Base

Fully upholstered swivel chair. Gas pneumatic lift. Adjustable height. Seat: Width 20¼" 514mm at center, Depth 17½" 445mm.

Seat: Soft urethane foam molded over rigid urethane and steel.

Backs: Outback standard with saddle stitch detail around the perimeter for fabric upholstered shells. Leather and leather alternative upholstered shells have saddle stitching accentuating the "V" detail on outback. *All **COM/COL** fabrics must be preapproved by Bernhardt Design prior to application.

Base: Polished aluminum or matte black powdercoat. Swivel/tilt mechanism and gas pneumatic lift with ¼" 108mm stroke mounted on 26¾" 680mm 5-star cast aluminum base with polished or black finish. Black dual wheel casters with caps coordinating with base finish. Approved for GSA. Contract GS-27F-010GA. GREENGUARD Certified.

I.a.m.



Seat Height	Arm Height	W	D	H	Fabric	Leather	Weight	Cubes/Qty
17¼-21½"	24-28¼"	23"	24"	33½-37¾"	1.75 yds.	24.0'	50 lbs.	28.98' / 1
438-546 mm	610-718 mm	584 mm	610 mm	851-959 mm	1.6 m	2.2 sqm	22.7 kg	.82 cu.

COM	COL	1	2	3	4	5	6	7	8	9	10	11
1250	1285	1375	1394	1418	1431	1445	1453	1464	1482	1511	1538	1622

588 Arm and Base. Polished Aluminum

589 Arm and Base. Matte Black Powdercoat

Fully upholstered swivel chair. Gas pneumatic lift. Adjustable height. Seat: Width 20¼" 514mm at center, Depth 17½" 445mm.

Seat: Soft urethane foam molded over rigid urethane and steel.

Backs: Outback standard with saddle stitch detail around the perimeter for fabric upholstered shells. Leather and leather alternative upholstered shells have saddle stitching accentuating the "V" detail on outback. *All **COM/COL** fabrics must be preapproved by Bernhardt Design prior to application.

Arm and Base: Polished aluminum or matte black powdercoat. Swivel/tilt mechanism and gas pneumatic lift with ¼" 108mm stroke mounted on 26¾" 680mm 5-star cast aluminum base with polished or black finish. Black dual wheel casters with caps coordinating with base finish. Approved for GSA. Contract GS-27F-010GA. GREENGUARD Certified.